

BA-802 / CERAMIC TOP CERAMIC PRIMER

PRODUCT DESCRIPTION

It is an acrylic dispersion based primer with high adhesion strength, used to increase adherence before the application of ceramic over ceramic coating.

AREAS OF USAGE

Bestkim BA-802 Ceramic Primer is used on glassy surfaces such as ceramics, mosaics, marble, wood, exposed concrete.

FEATURES

Provides high adherence strength. It is ready to use. It provides better adhesion of the ceramic adhesive to the surface. Does not contain solvent.

TECHNICAL SPECIFICATIONS

(23 ± 2°C and 50±5% relative humidity)

Color: Red

Shape: Liquid Density: 1.50 kg/lit

Application temperature: 5 - 30 C°

Temperature Resistance: (-30) - (70 C°)

Consumption : 100-125 gr/m² Drying

Time: 1 hour

Full drying time: 5 hours

SHELF LIFE:

12 months in its unopened original package.

SURFACE PREPARATION

The surface to be applied must be cured. The surface must be cleared of residues that will prevent adhesion. The surface must be moisture-free, dust-free, dry and clean. If there are cracks on the surface, they should be repaired with repair mortar.

EQUIPMENT CLEANING

After the application, The mortar on the equipment used should be cleaned with water before it dries.

PACKAGING

1kg. Plastic Bucket

SHELF LIFE

(Powder and liquid) 12 months in its unopened package in a dry environment.

STORAGE CONDITIONS

It should be stored in a dry, cool environment, protected from sun and frost. DISPOSAL Empty packaging can be disposed of in collection boxes according to local-local regulations or recycling rules. Dispose of the used waste material as construction waste after drying and hardening. It is dangerous to destroy product residues by burning.

SAFETY RECOMMENDATIONS

Please refer to the Safety Data Sheet (SDS) for easy and safe application of the product. Do not contact eyes. It is recommended to use suitable gloves, goggles and masks during use.

WARNINGS AND RECOMMENDATIONS

After application, it should be protected from adverse weather conditions such as direct sunlight, strong wind, high air temperature and frost. It is not suitable for use on surfaces that are constantly exposed to water. Do not add foreign matter from the application. Immediately after, hands and equipment should be washed with plenty of water. Keep mouth closed.

APPLICATION INSTRUCTIONS

In its own package or in a clean container, with a low-speed mixer for 3 minutes. mix. It is applied to the surface to be applied as a single layer with the help of a brush or roller. If the surface is very absorbent, a second coat can be applied after it has completely dried. It is a ready-to-use primer; it cannot be diluted with water.

CERTIFICATE OF CONFORMITY

