

BA-804 / DECORATIVE PLASTER PRIMER

PRODUCT DESCRIPTION

It is an acrylic copolymer emulsion based white colored coating primer with high adherence strength.

AREAS OF USAGE

Bestkim BA-804 Decorative Plaster Primer is used on interior and exterior thermal insulation systems before mineral plaster applications.

FEATURES / ADVANTAGES

Provides high adherence strength.

Facilitates adhesion with decorative coatings.

It has high covering power.

It hardens the application surface and increases adhesion.

TECHNICAL SPECIFICATIONS

(23 ± 2°C and 50±5% relative humidity)

Color: White

Shape: Liquid

Density: 1.55 kg/lit

Application temperature: 5 - 30 C°

Temperature Resistance: (-30) - (70 C°)

Consumption : 200-300 gr/m² (in each layer)

Drying Time: 6 hours

Shelf life: 12 months in its unopened original package.

REFERENCE STANDARDS

Approvals/Standards EN 1504-2

SURFACE PREPARATION

The application surface must be cured. The surface must be cleared of residues that will prevent adhesion. The surface must be moisture-free, dry and clean.

EQUIPMENT CLEANING

After application, The mortar on the equipment should be cleaned with water before it dries.

PACKAGING

20 kg Plastic Bucket

SHELF LIFE

(Powder and liquid) 12 months in its unopened package in a dry environment.

STORAGE CONDITIONS

It should be stored in a dry, cool environment, protected from sun and frost. DISPOSAL Empty packaging can be disposed of in collection boxes according to local-local regulations or recycling rules. Dispose of the used waste material as construction waste after drying and hardening. It is dangerous to destroy product residues by burning.

SAFETY RECOMMENDATIONS

Please refer to the Safety Data Sheet (SDS) for easy and safe application of the product. Do not contact eyes. It is recommended to use suitable gloves, goggles and masks during use.

WARNINGS AND RECOMMENDATIONS

After application, it should be protected from adverse weather conditions such as direct sunlight, strong wind, high air temperature and frost. Do not add foreign matter. Hands and used equipment should be washed with plenty of water immediately after the application. mouth closed keep it somehow.

APPLICATION INSTRUCTIONS

In its own package or in a clean container, with a low-speed mixer for 3 minutes. mix. It is applied to the surface to be applied as a single layer with the help of a brush or roller. It is a ready-to-use primer. If desired, it can be thinned with clean water at the rate of 5% by weight.

CERTIFICATE OF CONFORMITY

